

NORDIA WASH



- Nordia is an outdoor recessed downlight available either round or square.
- It has minimal aesthetic.
- Body material: aluminium.
- Trim material: Either aluminium electrostatically painted (white, black or other RAL finishes on request) or stainless steel AISI 316.
- Power cable HO5RN-F 2x0.75mm² L= 1m
- Cable outer diameter: 6.5mm
- Cable gland: IP67
- Safety Glass: 6mm
- Optics available: lenses
- 3 SDCM
- L90/B10 50000h
- Ingress Protection: IP67
- IK Rate: IK07



IP67

Model	Power	CCT	CRI80, CRI90 LED Source		Beam Angle	Shape	Type	Colour*	Dimming Option**	Extras
			80 (80)	90 (90)						
NORDIA WASH (NORDIA W)	4.1W (4)	2700K (27C) 3000K (30C) 4000K (40C) 5000K (50C)	440lm 440lm 475lm 410lm	355lm 380lm 410lm 440lm	Assymetric (AS) 27°x42°	Round (RD) Square (SQ)	Fixed (FX)	White (WH) Black (BL) Stainless (SS) Steel	Without Driver (00) 2448VDC Non Dimmable (2448ND) 24VDC PWM Dimmable (24DM) 48VDC PWM Dimmable (48DM) 230V Non Dimmable (230ND)	No Extras (0) Emergency Kit (1)

* Other RAL finishes available on request.

** With external IP68 casing box Dali, Phase cut, 1-10V dimming also possible.

Ordering Code Example: NORDIA W4-30C-90-AS-RD-FX-SS-00-0

