

- Nordia is an outdoor recessed downlight available either round or square.
- Nordia is also available in antiglare version in Black and White colour.
- Body material: aluminium.
- Trim material: Either aluminium electrostatically painted (white, black or other RAL finishes on request) or stainless steel AISI 316.
- The luminaire can be customized with the use of softening lens, line spread lens and honeycomb supplied as extra.
- Power cable HO5RN-F 2x0.75mm² L= 1m
- Cable outer diameter: 6.5mm
- Cable gland: IP67
- Safety Glass: 6mm
- Optics available: lenses
- UGR<19 (6°, 15°, 30°, 46°)
- 3 SDCM
- L90/B10 50000h
- Ingress Protection: IP67
- IK Rate: IK07



IP67

Model	Power	CCT	CRI80, CRI90 LED Source	Beam Angle	Shape	Type	Colour*	Dimming Option**	Accessories
			80 (80) 90 (90)						
NORDIA (NORDIA)	4.1W (4)	2700K (27C)	440lm 355lm	6° (06)	Round (RD)	Fixed (FX)	White (WH)	Without Driver (00)	COVER Standard (0/1) Honeycomb (1/1) Softening lens (2/1) Line spread lens (3/1) ↓ (XX) EXTRAS No Extras (1/0) Emergency Kit (1/1)
		3000K (30C)	440lm 380lm		Square (SQ)		Black (BL)	230VAC Non Dimmable (230ND)	
		4000K (40C)	475lm 410lm				Stainless (SS)	24V/48DC Non Dimmable (2448ND)	
		5000K (50C)	510lm 440lm				Steel	24VDC PWM Dimmable (24DM)	
								48VDC PWM Dimmable (48DM)	
	6.5W (7)	2700K (27C)	713lm 570lm	15° (15)				Without Driver (00)	
		3000K (30C)	713lm 615lm	30° (30)				230VAC Non Dimmable (230ND)	
		4000K (40C)	765lm 660lm	46° (46)				24V/48DC Non Dimmable (2448ND)	
		5000K (50C)	765lm 713lm					24VDC PWM Dimmable (24DM)	
								48VDC PWM Dimmable (48DM)	
			6500K (65C)	765lm -					



* Other RAL finishes available on request.

** With external IP68 casing box Dali, Phase cut, 1-10V dimming also possible.

Ordering Code Example: NORDIA 7-30C-90-46-RD-FX-SS-00-10

