

- Oscar D round inground luminaire is ideal for a soft floor wash in pathways.
- Available in two sizes $\Phi 55$ and $\Phi 25$ mm.
- It has a minimal aesthetic with no visible screws.
- Body material : stainless steel 316 or brass.
- Front cover: stainless steel 316 or brass.
- Mounting box: Plastic frame casing.
- 24VDC PWM dimmable
- Power cable: H05RN-F 2x0.75mm L=30cm
- Ingress Protection: IP67
- IK Rate: IK10

L90/B10 >50.000h

OSCAR D



OSCAR MINI D



OSCAR D



IP67

Model	Type	CCT	CRI80, CRI90 LED Source		Beam Angle	Colour	Dimming Option*
OSCAR D 2.5W <i>(OSCAR D3)</i>	Round (RD)	2700K (27)	275lm	245lm	20° (20)	Stainless Steel (SS)	24VDC PWM Dimmable (24)
		3000K (30)	295lm	260lm	35° (35)	Brass (BR)	
		4000K (40)	315lm	280lm	60° (60)		
		5000K (50)	330lm	295lm			

*Maximum parallel connection up to 15pcs per PWM dimmer.

Ordering Code Example: OSCAR D3-RD-30-80-35-SS-24

OSCAR MINI D



IP67

Model	Type	CCT	CRI80, CRI90 LED Source		Beam Angle	Colour	Dimming Option*
OSCAR MINI D 1W <i>(OSCAR MINI D1)</i>	Round (RD)	2700K (27)	120lm	105lm	17° (17)	Stainless Steel (SS)	24VDC PWM Dimmable (24)
		3000K (30)	125lm	110lm	25° (25)	Brass (BR)	
		4000K (40)	135lm	120lm	35° (35)		
		5000K (50)	140lm	125lm			

*Maximum parallel connection up to 15pcs per PWM dimmer.

Ordering Code Example: OSCAR MINI D1-RD-30-80-35-SS-24

OSCAR D



OSCAR MINI D

