

# OUTLINER 20

Outliner series is a complete series of custom made linear luminaires with Transparent, Milky Satin or Microprismatic cover. It is available in 4 different widths of 20, 30, 40, 50mm (luminous area widths). It is offered in standard and in custom lengths. The series offers an excellent uniformity with colour consistency.


- Multiple mounting options (fixed, surface, wall brackets or pendant).
- Long & Short bracket accessories available for wall installation.
- L90/B10 >50.000h (for monochromatic models).
- 3 SDCM (for monochromatic models).
- Ingress Protection: IP40

Lighting management options:  
On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth

**L90/B10 >50.000h**  
for monochromatic models

***Available upon request:***

- ✓ Custom dimensions
- ✓ Custom luminaire colours




Seamless


## STANDARD




FIXED




SURFACE



WALL BRACKET  
(Long/Short)



PENDANT




**ELA.008**  
ANTISLIPPER  
for vertical installation  
(as extra)


## SEAMLESS




FIXED




FIXED ELEVATED




SURFACE



WALL BRACKET  
(Long/Short)



PENDANT



**ELA.008**  
ANTISLIPPER  
for vertical installation  
(as extra)



**PRH.027**  
COUPLER accessory  
(as extra)

## Connectors



Input cable with IP connectors  
supplied as extra



In-Out cables & waterproof connectors  
supplied as extra.



Supply connectors for a luminaire array  
(as extra)

**CNC.009** 2 pole connector (monochrome)  
**CNC.013** 4 pole connector (RGB)  
**CNC.053** 5 pole connector (RGBW)

STANDARD



Model	Luminaire Colour*	Colour Temperature	CRI	Watt* / Length	Type	Voltage
<b>OUTLINER 20 FIXED</b> (OUTLINER20-F)  <b>OUTLINER 20 SURFACE</b> (OUTLINER20-S)  <b>OUTLINER 20 SHORT BRACKET 6.5cm</b> (OUTLINER20-B1)  <b>OUTLINER 20 LONG BRACKET 11.5cm</b> (OUTLINER20-B2)  <b>OUTLINER 20 PENDANT</b> (OUTLINER20-P1) <b>H:150cm</b> (OUTLINER20-P2) <b>H:300cm</b>	Anodized (AN)	2000K (20)	≥ 80 (80)	10.5W / 53cm (11W053)	Transparent (TR) Milky Satin (MS) Microprismatic (MP)	24VDC (24)
	White (WH)	2500K (25)		17.5W / 86.3cm (18W086)		
	Black (BL)	2700K (27)		21W / 103cm (21W103)		
		3000K (30)		24.5W / 119.7cm (25W120)		
		4000K (40)		31.5W / 153cm (32W153)		
		5700K (57)	42W / 203cm (42W203)			
<i>RGBWW / RGBCW / RGB</i>						
		Colour	Watt / Length			
		RGBWW (RGBWW)	13.5W / 53cm (14W053)			
		RGBCW (RGBCW)	23.1W / 88.7cm (23W089)			
		84LED/m	27W / 103cm (27W103)			
			32.8W / 124.4cm (33W124)			
			40.5W / 153cm (41W153)			
			54W / 203cm (54W203)			
		RGBWW (RGBWW)	9.7W / 53cm (10W053)			
		RGBCW (RGBCW)	15.6W / 83cm (16W083)			
		60LED/m**	19.5W / 103cm (20W103)			
			23.4W / 123cm (23W123)			
			29.2W / 153cm (29W153)			
			39W / 203cm (39W203)			
		RGB (RGB96)	11.5W / 53cm (12W053)			
		96LED/m	20.1W / 90.5cm (20W091)			
			23W / 103cm (23W103)			
			27.3W / 121.7cm (27W122)			
			34.5W / 153cm (35W153)			
			46W / 203cm (46W203)			
		RGB (RGB60)	7.2W / 53cm (07W053)			
		60LED/m**	11.6W / 83cm (12W083)			
			14.5W / 103cm (15W103)			
			17.4W / 123cm (17W123)			
			21.7W / 153cm (22W153)			
			29W / 203cm (29W203)			
		RGB (RGB30)	3.6W / 53cm (04W053)			
		30LED/m**	5.7W / 83cm (06W083)			
			7.2W / 103cm (07W103)			
			8.6W / 123cm (09W123)			
			10.8W / 153cm (11W153)			
			14.4W / 203cm (14W203)			
						12VDC (12)

\* Available in other colours or/and power upon request.

\*\* The LED density of these ribbons is low thus, the homogeneity of lighting surface of Milky type luminaire will be affected.

Ordering Code Example: OUTLINER20 B2-AN-RGB60-17W123-MP-24

