




- POT is a recessed adjustable downlight.
- Luminaire outer trim material: aluminium.
- Outer trim available in black or white as standard but custom colours also available upon request.
- POT DEEP version is also available for LED lamps.
- 3 SDCM
- L90/B10 50000h
- Low UGR ensuring visual comfort (UGR < 15 for DEEP version models).
- IP20

Name	Model	CCT	CRI80, CRI90 LED Source	Beam Angle	Luminaire Colour	Dimming Option	Accessories
POT (POT)	Low Depth 7W (LD7)	2700K (27C)	930lm 762lm	31°x35° (35)	White (WH) Black (BL)	Without Driver (00) Non Dimmable (ND) Analogue (1-10V) (A1) DMX (DX) DALI (DL) Push Button (PB) Phase Cut (PC) Wireless* (WL)	
		3000K (30C)	960lm 792lm				
		4000K (40C)	1020lm 840lm				
		5000K (50C)	1020lm 840lm				
	Standard 6.2W (ST6)	2700K (27C)	704lm 568lm	20°x28° (28) 32°x42° (42) 42°x50° (50)			
		3000K (30C)	713lm 608lm				
		4000K (40C)	760lm 656lm				
		5000K (50C)	736lm 704lm				
	Standard 12.2W (ST12)	2700K (27C)	1590lm 1380lm				
		3000K (30C)	1710lm 1485lm				
		4000K (40C)	1830lm 1590lm				
		5000K (50C)	1710lm 1590lm				
Standard 18W (ST18)	2700K (27C)	2067lm 1794lm					
	3000K (30C)	2223lm 1931lm					
	4000K (40C)	2379lm 2067lm					
	5000K (50C)	2223lm 2067lm					
Narrow Beam 6W (NB6)	2700K (27C)	616lm 497lm	8°x12° (12)				
	3000K (30C)	616lm 532lm					
	4000K (40C)	665lm 574lm					
	5000K (50C)	714lm 616lm					
Narrow Beam 8W (NB8)	2700K (27C)	792lm 639lm					
	3000K (30C)	792lm 684lm					
	4000K (40C)	855lm 738lm					
	5000K (50C)	918lm 792lm					
Zoom 6.4W (ZM6)	2700K (27C)	704lm 568lm	17°x23°-35°x45° (23-45)				
	3000K (30C)	713lm 608lm					
	4000K (40C)	760lm 656lm					
	5000K (50C)	736lm 704lm					
Zoom 13W (ZM13)	2700K (27C)	1306lm 1098lm					
	3000K (30C)	1360lm 1150lm					
	4000K (40C)	1435lm 1236lm					
	5000K (50C)	1453lm 1236lm					
Warm Dimming 0.2-6W (WD6)	1800K-3000K (1830B)	636lm 518lm	90 (90) 95 (95) 20°x28° (28) 32°x42° (42) 42°x50° (50)	Analogue (1-10V) (A1) DALI (DL) Phase Cut (PC) Wireless* (WL)			
	1800K-3000K (1830B)	1246lm 1045lm					
Warm Dimming 12W (WD12)	1800K-3000K (1830B)	1246lm 1045lm					
Tunable White 5.9W (TW6)	2700K-5000K (2750B)	585lm (both CCT's driven)		DALI (DL) Wireless* (WL)			
Tunable White 11.5W (TW12)	2700K-5000K (2750B)	987lm (both CCT's driven)					



* The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: POT-ST18-30C-80-42-WH-DL-100

POT DEEP LL

IP20

Model	Luminaire Colour:	Lamp Holder	Accessories
POT DEEP LL <i>(POT DEEP LL)</i>	White/White (WW) White/Black (WB) Black/Black (BB) Black/White (BW)	GU10 (max 7.5W) (G1)	<p>COVER</p> <ul style="list-style-type: none"> Standard (0x) Honeycomb (1x) Linear Spread (2x) Softening Lens (3x) <p>IP RATE</p> <ul style="list-style-type: none"> IP20 (x0)




Ordering Code Example: **POT DEEP LL-WW-G1-10**






POT WH


LD7



ST6/ ST12/ ST18/ WD6/ WD12/ TW6/ TW12



NB6/ NB8



ZM6/ ZM13

