

- LED module ideal for most GU10/MR16 luminaires
- Easy replacement on existing projects
- High efficiency
- Available in four different beam angles
- Available with different dimming options flexible for any project requirement.
- L90/B10 50.000h
- 3SDCM
- IP44 (face only)



Model	LED Power	CCT*	CRI80, CRI90 LED Source	Beam Angle	Colour**	Dimming Option	Extra
<b>REFIT MODULE</b> <i>(REFIT M)</i>	<b>6.1W</b> (6)	2700K (27B) 3000K (30B) 4000K (40B)	812lm 677lm 845lm 705lm 879lm 733lm	80 (80) 90 (90)	White (WH)	Without Driver (00)	No Extras (00)
				18° (18)	Black (BL)	Non Dimmable (ND)	Emergency (01)
				24° (24)		Analogue (1-10V) (A1)	
				34° (34)		DMX (DX)	
				56° (56)		DALI (DL)	
						Push Button (PB)	
						Phase Cut (PC)	
						Wireless*** (WL)	

\* CCT: 3500K, 5000K, 6500K available upon request.

\*\* Other RAL colours available upon request.

\*\*\* The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: REFIT M6-30B-80-24-WH-ND-00

