



- REVO L is the large recessed downlight of REVO series.
- It is available in white or black colour.
- It is offered monochromatic, tunable white or warm dimming.
- It has a variety of dimming options.
- Low UGR ensuring visual comfort (UGR < 18).

Monochromatic, TW, WD

- 3 SDCM
- L90/B10 50.000h



Model	LED Power	CCT*	CRI LED Source fc:55°C	Type	Beam Angle	Colour	Dimming Option	
			80 (80) 90 (90)					
REVO L (REVO L)	24W (24)	2700K (27B)	3600lm 2970lm	Fixed (FX)	25° (25) 36° (36) 60° (60)	White (WH) Black (BL)	Without Driver (00)	
		3000K (30B)	3810lm 3100lm				Non Dimmable (ND)	
		4000K (40B)	3940lm 3280lm				Analogue (1-10V) (A1)	
		5700K (57B)	3980lm 3260lm				DMX (DX) DALI (DL) Phase Cut (PC) Push Button (PB) Wireless** (WL)	
	32W (32)	2700K (27B)	4500lm 3710lm			90 (90)	Without Driver (00)	
		3000K (30B)	4780lm 3870lm					DMX (DX)
		4000K (40B)	4910lm 4100lm					DALI (DL)
		5700K (57B)	4970lm 4090lm					Wireless** (WL)
	Tunable White 32W (TW32)	2700K~5700K (2757B)	2940lm (Both CCTs driven)			Without Driver (00)		
			3190lm (Both CCTs driven)				DMX (DX) DALI (DL) Wireless** (WL)	
	Tunable White 37W (TW37)					Without Driver (00)		
							Analogue (1-10V) (A1) DMX (DX) DALI (DL) Phase Cut (PC) Push Button (PB) Wireless** (WL)	
Warm Dimming 24W (WD24)	1800K~3000K (1830B)	2250lm		Without Driver (00)				
		2890lm			Analogue (1-10V) (A1) DMX (DX) DALI (DL) Phase Cut (PC) Push Button (PB) Wireless** (WL)			
Warm Dimming 31W (WD31)	1800K~3000K (1830B)			Without Driver (00)				
					Analogue (1-10V) (A1) DMX (DX) DALI (DL) Wireless** (WL)			
RGBW 22W (RGBW22)			1545lm		40° (40) 65° (65)		Without Driver (00) DMX (DX) DALI (DL) Wireless** (WL)	
RGBW 29.5W (RGBW30)			2075lm					

* Models with CCTs of 3500K, 5000K & 6500K are available upon request.
** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: REVO L-37-30B-80-FX-36-WH-DL

Warm dimming 3000K to 1800K

