



- REVO M is the second recessed downlight of REVO series.
- It is available in white or black colour.
- It is offered monochromatic, tunable white or warm dimming.
- It has a variety of dimming options.
- Low UGR ensuring visual comfort (UGR < 18).

#### Monochromatic, TW, WD

- 3 SDCM
- L90/B10 50.000h



Model	LED Power	CCT*	CRI LED Source fc:55°C	Type	Beam Angle	Colour	Dimming Option
			80 (80) 90 (90)				
<b>REVO M</b> (REVO M)	<b>17W</b> (17)	2700K (27B)	2530lm 2080lm	Fixed (FX)	22° (22) 36° (36) 60° (60)	White (WH) Black (BL)	Without Driver (00)
		3000K (30B)	2680lm 2180lm				Non Dimmable (ND)
		4000K (40B)	2760lm 2300lm				Analogue (1-10V) (A1)
		5700K (57B)	2790lm 2290lm				DMX (DX) DALI (DL)
	<b>24W</b> (24)	2700K (27B)	3600lm 2970lm				Phase Cut (PC)
		3000K (30B)	3810lm 3100lm				Push Button (PB)
4000K (40B)		3940lm 3280lm	Wireless** (WL)				
<b>32W</b> (32)	2700K (27B)	4500lm 3710lm				Wireless** (WL)	
	3000K (30B)	4780lm 3870lm					
	4000K (40B)	4910lm 4100lm					
<b>Tunable White</b> <b>23.4W</b> (TW23)	2700K~5700K (2757B)	90 (90)					Without Driver (00)
		2310lm (Both CCTs driven)					DMX (DX) DALI (DL) Wireless** (WL)
<b>Tunable White</b> <b>32W</b> (TW32)		2890lm (Both CCTs driven)					
<b>Warm Dimming</b> <b>24W</b> (WD24)	1800K~3000K (1830B)	95 (95)					Without Driver (00)
		2210lm					Analogue (1-10V) (A1)
<b>Warm Dimming</b> <b>31W</b> (WD31)	1800K~3000K (1830B)	2840lm					DMX (DX) DALI (DL) Phase Cut (PC) Push Button (PB) Wireless** (WL)
<b>RGBW 22W</b> (RGBW22)		1545lm			40° (40) 65° (65)		Without Driver (00) DMX (DX) DALI (DL) Wireless** (WL)
<b>RGBW 29.5W</b> (RGBW30)		2075lm					

\* Models with CCTs of 3500K, 5000K & 6500K are available upon request.  
\*\* The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: REVO M-24-30B-90-FX-60-WH-DL

Warm dimming 3000K to 1800K

