

- RODITA downlight with a tilt of 60°.

### Monochromatic:

- High efficiency deep reflector.
- Luminaire body: aluminium.
- 3 SDCM (for monochromatic models).
- L90/B10 50.000h

### RGBW:

- White CCT at 4000K. (Other CCTs are available upon request).
- L80/B10 50.000h



Model	LED Power	CCT*	LED Source			Type	CRI	Beam Angle	Colour	Dimming Option	Accessories
RODITA (RODITA)	12.3W (12)	2700K (27B)	1662lm	1372lm	1216lm	Adjustable (AD)	80 (80)	40° (40)	White (WH)	Without Driver (00)	COVER Standard (0:1)  EXTRAS No Extras (X:0) Emergency**** (X:1)
		3000K (30B)	1766lm	1434lm	1299lm		90 (90)			Analogue (1-10V) (A:1)	
		4000K (40B)	1818lm	1517lm	-		97 (97)			DMX (DX)	
		5700K (57B)	1766lm	-	-		DALI (DL)			Push Button (PB)	
							Phase Cut (PC)				
					Wireless*** (WL)						
									Without Driver (00)		
									DMX (DX)		
									DALI (DL)		
									Wireless*** (WL)		



12.5W (13) RGBW (RGBW) 960lm


\* BRIDGELUX: Models with CCTs of 3500K, 5000K & 6500K are available upon request.

\* CREE RGBW: Other colour combinations available upon request.

\*\* The wireless dimming option includes driver and Bluetooth dimming accessory.

\*\*\*\* Emergency only for monochromatic versions.

Ordering Code Example: RODITA 12-40B-AD-80-40-WH-DL-00



Monochromatic

RGBW

