

- ROLL Wash outdoor luminaire suitable for surface installation.
- It has minimal aesthetic with no visible screws.
- It is available in black or white colour as standard but RAL colours are also available upon request.
- Marine treatment is also available upon request ensuring higher resistance to weather, UV, water and mould growth.
- Body material: aluminium.
- Power supply cable required: 3x0,75mm² with maximum external diameter 7mm.
- 3 SDCM
- L90/B10 50000h
- Ingress Protection: IP65



IP65

Model	LED Power	CCT	CRI80, CRI90 LED Source		Beam Angle	Shape	Type	Colour*	Dimming Option
			80 (80)	90 (90)					
ROLL WASH <i>(ROLL W)</i>	4.1W (04)	2700K (27C) 3000K (30C) 4000K (40C) 5000K (50C)	440lm 440lm 475lm 475lm	355lm 380lm 410lm 440lm	Asymmetric (AS) 27°x42°	Round (RD)	Fixed (FX)	Black (BL) White (WH)	Without Driver (00) 230V Non Dimmable (230ND) 24VDC PWM Dimmable (24DM) 48VDC PWM Dimmable (48DM)

* Available in RAL colours upon request.

Ordering Code Example: ROLL W 04-30C-80-AS-RD-FX-BL-230ND-0

