

# STANDARD SERIES 108, 84, 60, 48 LED/m


## RGBW-RGBWW-RGBCW 4in1 chip

Lighting management options:  
DALI/DMX512/PHASE CUT/IR/RF/Bluetooth



Adjustable CCT  
RGBW, RGBWW, RGBCW

24VDC

Code	No.LED/m	Watt/m	Reel(m)	CCT		Voltage	Beam Angle	 * (mm)	IP Rate
<i>IP20</i>									
<b>TIV.240</b> /CA	84	27W	5	RGBWW 4in1 (2700K)	Adjustable	24VDC	120°	71.5	IP20
<b>TIV.241</b> /CA	60	19.5W	5	RGBWW 4in1 (2700K)	Adjustable	24VDC	120°	100	IP20
<b>TIV.243</b> /CA	84	27W	5	RGBCW 4in1 (6000K)	Adjustable	24VDC	120°	71.5	IP20
<b>TIV.244</b> /CA	60	19.5W	5	RGBCW 4in1 (6000K)	Adjustable	24VDC	120°	100	IP20
<b>TIV.534</b> /CA	108	15W	5	RGBW 4in1 (2700K)	Adjustable	24VDC	120°	50.5	IP20
<i>IP65</i>									
<b>TIV.242</b> /CA	48	15.4W	5	RGBWW 4in1 (2700K)	Adjustable	24VDC	120°	125	IP65
<b>TIV.245</b> /CA	48	15.4W	5	RGBCW 4in1 (6000K)	Adjustable	24VDC	120°	125	IP65
<b>TIV.533</b> /CA	108	15W	5	RGBW 4in1 (2700K)	Adjustable	24VDC	120°	50.5	IP65

\* Please confirm the connection points on the modules.

