

STANDARD SERIES 60LED/m

Monochromatic 3CHIP



Lighting management options:
On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth



Monochromatic 3chip 24VDC

Code	No.LED/m	Watt/m	Reel(m)	CCT/Colour*	Luminus FLUX (lm/m)	Voltage	Beam Angle	* (mm)	IP Rate**
<i>IP20</i>									
TIV.222	60	14.4W	5	2600-2900K	730	24VDC	120°	100	IP20
TIV.189	60	14.4W	5	2900-3300K	780	24VDC	120°	100	IP20
TIV.217	60	14.4W	5	3900-4300K	840	24VDC	120°	100	IP20
TIV.188	60	14.4W	5	5700-6300K	950	24VDC	120°	100	IP20
TIV.227	60	14.4W	5	BLUE	-	24VDC	120°	100	IP20
TIV.228	60	14.4W	5	RED	-	24VDC	120°	100	IP20
<i>IP65</i>									
TIV.223	60	14.4W	5	2600-2900K	700	24VDC	120°	100	IP65
TIV.193	60	14.4W	5	2900-3300K	740	24VDC	120°	100	IP65
TIV.218	60	14.4W	5	3900-4300K	800	24VDC	120°	100	IP65
TIV.192	60	14.4W	5	5700-6300K	900	24VDC	120°	100	IP65

* Available in other colours upon request
** Please confirm the connection points on the modules

