

STANDARD SERIES 60LED/m

Monochromatic

Lighting management options:
On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth



Monochromatic 12VDC

Code	No.LED/m	Watt/m	Reel(m)	CCT/Colour*	Luminous FLUX (lm/m)	Voltage	Beam Angle	✂ *(mm)	IP Rate**
<i>IP20</i>									
TIV.249	60	4.8W	5	2200-2400K	240	12VDC	120°	50	IP20
TIV.206	60	4.8W	5	2600-2900K	260	12VDC	120°	50	IP20
TIV.143	60	4.8W	5	2900-3300K	280	12VDC	120°	50	IP20
TIV.214	60	4.8W	5	3900-4300K	310	12VDC	120°	50	IP20
TIV.142	60	4.8W	5	5700-6300K	350	12VDC	120°	50	IP20
TIV.141	60	4.8W	5	RED	-	12VDC	120°	50	IP20
TIV.140	60	4.8W	5	GREEN	-	12VDC	120°	50	IP20
TIV.139	60	4.8W	5	BLUE	-	12VDC	120°	50	IP20
TIV.144	60	4.8W	5	AMBER	-	12VDC	120°	50	IP20
<i>IP65</i>									
TIV.250	60	4.8W	5	2200-2400K	240	12VDC	120°	50	IP65
TIV.219	60	4.8W	5	2600-2900K	240	12VDC	120°	50	IP65
TIV.162	60	4.8W	5	2900-3300K	260	12VDC	120°	50	IP65
TIV.215	60	4.8W	5	3900-4300K	290	12VDC	120°	50	IP65
TIV.161	60	4.8W	5	5700-6300K	225	12VDC	120°	50	IP65
TIV.158	60	4.8W	5	RED	-	12VDC	120°	50	IP65
TIV.163	60	4.8W	5	BLUE	-	12VDC	120°	50	IP65
TIV.198	60	4.8W	5	AMBER	-	12VDC	120°	50	IP65

* Available in other colours upon request

** Please confirm the connection points on the modules

