

TALUS



- TALUS fixed downlight is available for surface or pendant installation.
- With a consumption of up to 31W is suitable for applications that require high lumen output.
- Available in black or white colour.
- 3 SDCM
- L90/B10 50.000h



LIGHTSOURCE BY
bridgelux.

Model (LED Power)	CCT*	CRI80, CRI90 LED Source	Type	Beam Angle	Colour	Dimming Option	Accessories
		80 (80) 90 (90)					
TALUS Surface 23.9W (TALUS SF 24)	2700K (27B) 3000K (30B) 4000K (40B) 5700K (57B)	3621lm 2987lm 3847lm 3123lm 3960lm 3304lm 3847lm -	Fixed (FX)	20° (20) 40° (40) 60° (60)	White (WH) Black (BL)	Without Driver (00) Non Dimmable (ND) Analogue (1-10V) (A1) DMX (DX) DALI (DL) Push Button (PB) Phase Cut (PC)	ANTI-GLARE SHIELD White Matt (1X) Black Matt (2X) Gold Matt (3X) ↓ (XX) ↑ EXTRAS No Extras (X0)
TALUS Pendant 23.9W (TALUS PD 24)							
TALUS Surface 31.3W (TALUS SF 31)	2700K (27B) 3000K (30B) 4000K (40B) 5700K (57B)	4510lm 3721lm 4792lm 3890lm 4933lm 4115lm 4792lm -					
TALUS Pendant 31.3W (TALUS PD 31)							
Warm Dimmable							
		CRI95 LED Source					
TALUS WD Surface 30.7W (TALUS WD SF 31)	Warm Dimmable 1800K-3000K (WD)	95 (95) 2840lm					
TALUS WD Pendant 30.7W (TALUS WD PD 31)							

* Models with CCTs of 3500K, 5000K & 6500K are available upon request.

Ordering Code Example: TALUS SF31-30B-80-FX-60-BL-DL-20

