


TETRA SLICK WASH

- TETRA SLICK WASH linear luminaire is available for surface or pendant application.
- L90/B10 50000h
- 3 SDCM
- Ingress Protection: IP40

Lighting management options:

On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth



Available upon request:

- ✓ Custom dimensions
- ✓ Custom luminaire colours
- ✓ Emergency version



Model	Luminaire Colour	CCT	CRI	Beam Angle	Watt-LED/m	Length	Voltage
TETRA SLICK WASH Surface <i>(TETRA SLICK WASH SF)</i>	Anodized <i>(AN)</i>	2700K <i>(27C)</i>	≥ 70* <i>(70)</i>	12° <i>(12)</i>	10.5W - 10LED/m <i>(1010)</i>	32cm <i>(032)</i>	24VDC <i>(24)</i>
	White <i>(WH)</i>	3000K <i>(30C)</i>	≥ 80** <i>(80)</i>	25° <i>(25)</i>	21W - 10LED/m <i>(2010)</i>	52cm <i>(052)</i>	
	Black <i>(BL)</i>	4000K <i>(40C)</i>		46° <i>(46)</i>	21W - 20LED/m <i>(2020)</i>	62cm <i>(062)</i>	
		5600K* <i>(56C)</i>		40°x10° <i>(40)</i>		82cm <i>(082)</i>	
TETRA SLICK WASH Wall Adjustable <i>(TETRA SLICK WASH WA)</i>						92cm <i>(092)</i>	
						102cm <i>(102)</i>	
						112cm <i>(112)</i>	
						122cm <i>(122)</i>	
						132cm <i>(132)</i>	
						142cm <i>(142)</i>	
						152cm <i>(152)</i>	
						162cm <i>(162)</i>	
						172cm <i>(172)</i>	
						182cm <i>(182)</i>	
TETRA SLICK WASH Pendant <i>(TETRA SLICK WASH PD)</i>					25.2W - 24LED/m <i>(2424)</i>	192cm <i>(192)</i>	
						202cm <i>(202)</i>	
						52cm <i>(052)</i>	
						102cm <i>(102)</i>	
						152cm <i>(152)</i>	
					202cm <i>(202)</i>		

* 5600K only available in CRI 70
** CRI 80 only for 2700K/3000K/4000K

Ordering Code Example: TETRA SLICK WASH SF-BL-30C-80-46-2424-102-24

