

ZERO-S is a low depth small inground luminaire.

- Housing: aluminum
- Front cover: stainless steel 316
- Glass : Tempered glass T=4mm
- Mounting box: aluminum
- Cable gland: PG7 cooper with nickel coated.
- Power cable: H05RN-F 2x0.75mm² L=1.5m
- IK Rate: 06
- Ingress Protection: IP67
- Maximum load 320kgs

Lighting management options:

On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth





IP67

| Code | No.LED | Watt | Lumen | Colour Temperature* | Dimensions | Diameter | Max. Kg | Voltage | Beam Angle** | IP Rate | |
|----------------|--------|------|-------|---------------------|------------|----------|---------|---------|--------------|---------|----------|
| LGR.132 | 1 | 3W | 110lm | 2700K | 54x40mm | 40mm | 1000Kg | 12VDC | 25° | IP67 | Dimmable |
| LGR.089 | 1 | 3W | 115lm | 3000K | 54x40mm | 40mm | 1000Kg | 12VDC | 25° | IP67 | Dimmable |
| LGR.088 | 1 | 3W | 130lm | 5600K | 54x40mm | 40mm | 1000Kg | 12VDC | 25° | IP67 | Dimmable |



*Other CCT available upon request.

**Available in 10°, 40° & 60° degrees upon request.



ACC.004
Diffused glass (as extra)