

ZERO is a small inground luminaire.

- Housing: aluminum
- Front cover: stainless steel 316
- Glass : Tempered glass T=4mm
- Mounting box: aluminum
- Cable gland: PG7 cooper with nickel coated.
- Power cable: H05RN-F 2x0.75mm² L= 1.5m
- IK Rate: 06
- Ingress Protection: IP67
- Maximum load 320kgs

Lighting management options:

On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth



CREE
LEDs


IP67

Code	No.LED	Watt	Lumen	Colour Temperature*	Dimensions	Diameter	Max. Kg	Voltage	Beam Angle	IP Rate	
LGR.133	1	3W	100lm	2700K	Φ40x75mm	40mm	1000Kg	12VDC	25°	IP67	Dimmable
LGR.091	1	3W	110lm	3000K	Φ40x75mm	40mm	1000Kg	12VDC	25°	IP67	Dimmable
LGR.090	1	3W	130lm	5600K	Φ40x75mm	40mm	1000Kg	12VDC	25°	IP67	Dimmable



*Other CCT available upon request.

**Available in 10°, 40° & 60° degrees upon request.



ACC.005
Diffused glass (as extra)